

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/062342 A3

(51) International Patent Classification⁷: **H01J 61/34**,
61/30, 61/82

(21) International Application Number:
PCT/JP2004/019484

(22) International Filing Date:
20 December 2004 (20.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-424170 22 December 2003 (22.12.2003) JP

(71) Applicant (for all designated States except US): **MAT-
SUSHITA ELECTRIC INDUSTRIAL CO., LTD.**
[JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka
5718501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KANAZAWA,**

Yukiya. UTSUBO, Atsushi. NOHARA, Hiroshi. KAK-
ISAKA, Shunsuke. NISHIURA, Yoshiharu.


(74) Agents: **NAKAJIMA, Shiro** et al.; 6F, Yodogawa
5-Bankan, 2-1, Toyosaki 3-chome, Kita-ku, Osaka-shi,
Osaka 5310072 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: METAL HALIDE LAMP AND LUMINAIRE USING THE SAME



(57) Abstract: The present invention aims at providing a metal halide lamp that (i) prevents a decline in the lumen maintenance and a deterioration of quality in appearance due to the coloring of a casing tube surrounding the arc tube, and at the same time (ii) achieves high luminous efficiency. A metal halide lamp (1) has a pair of electrodes (20a&b) placed in an arc tube (3) made of translucent ceramic, and a sodium halide is enclosed therein. The metal halide lamp (1) satisfies $L/D \geq 4$, where L (mm) is the length of the space between the electrodes (20a&b) and D (mm) is the internal diameter of the arc tube (3). The metal halide lamp (1) has a casing tube (2) surrounding the arc tube (3), at least around a portion between the electrodes (20a&b). Here, $R/r \geq 3.0$ is satisfied, where R is the internal diameter of the casing tube (2) and r is the external diameter of the arc tube (3), within a region positionally corresponding to, in a radial direction of the arc tube, the space between the electrodes (20a&b), on a cross-sectional surface where an outer circumference of the arc tube (3) comes closest to the internal circumference of the casing tube (2).



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

(88) Date of publication of the international search report:

6 October 2005